

Broome Wharf Information




- L Vertical Ladder
- L Multi- Staged Landings
- F Fuel (80 tonnes/hr)
- f Bowser (14 tonnes/hr)
- W Water (100mm 100 tonnes/l)
- w Water (50mm & 25mm 14 tonnes/hr)
- 🚿 Emergency Shower
- 🏥 First Aid
- MUSTER POINT Muster Point
- 🚻 Toilet
- Original Wharf load limits 3.4
- Wharf extension load limits 4.5
- Max wheel loads as per highway regulation
- SWL Bollards 50t
- SWL 70T Bollard
- SWL 35T Bollard d/t Pilings

Tides

Highest Astronomical Tide	10.63m
Mean High Water Springs	9.35m
Mean High Water Neaps	6.34m
Mean Low Water Neaps	4.59m
Mean Low Water Springs	1.63m
Lowest Astronomical Tide	0.15m


Jetty Dimensions

Jetty Dimensions	331 x 26m
Neck Light Height	9.0m
Jetty Neck Gate Width	6.9m



Berth pockets dimensions.

Berth 4,5,6	- 110 x 40m
Berths 2,3	- 70 x 22m
Berth 1	- 40 x 12m
Berth 11	- 65 x 20m



Max Draught dependant on tides - Refer to latest [KPA LMN](#) for declared berth depths.

Maximum Berthing Δ 50,000 MT
Larger vessels with permission

Disclaimer
All descriptions, dimensions and references to conditions and other details contained in this diagram are given in good faith and are believed to be true and correct, however they are provided as a guide only and should not be relied upon as representation of fact. Interested parties must satisfy themselves as to the accuracy of details by way of inspection or otherwise.

Copyright
This diagram including but not limited to all logos, graphics and text remains the property of Kimberley Ports Authority and must not be copied, modified, altered, amended or transferred without the express written permission of Kimberley Ports Authority.